



Dimension : mm

L Type	Torque		Max. rpm	D	L	L1	L2	d		GD kgf cm	Weight kgf
	Min.	Max.						Min.	Max.		
<b>L - 035</b>	0.05	0.15	6,000	16.1	20.5	6.5	7.5	4	8	0.1	0.04
<b>L - 050</b>	0.15	0.45	4,500	27	43.2	15.5	12.2	6	16	1.0	0.14
<b>L - 070</b>	0.3	0.9	3,600	35	49.2	18.5	12.2	6	20	3.3	0.27
<b>L - 075</b>	0.5	1.5	3,600	45	54.4	21	12.4	8	26	9.1	0.45
<b>L - 090</b>	0.8	2.4	3,000	54	55	21	13	10	28	15.0	0.60
<b>L - 095</b>	1.0	3.0	3,000	55	61	24	13	10	28	17.0	0.70
<b>L - 099</b>	2.0	6.0	3,000	66	73	30	18	12	36	42.0	1.40
<b>L - 100</b>	2.5	7.5	3,000	66	88	35	18	12	36	43.0	1.50
<b>L - 110</b>	5.0	15.0	2,500	85	110	44	22	12	48	147.0	3.00
<b>L - 150</b>	10.0	30.0	2,500	96	118.5	46	26.5	16	46	258.0	4.00
<b>L - 190</b>	15.0	45.0	2,000	115	138.5	56	26.5	16	58	628.0	6.90
<b>L - 225</b>	20.0	60.0	2,000	127	152.5	63.5	26.5	18	60	1685.0	10.45
<b>L - 276</b>	25.0	75.0	2,000	157	200	79	41	22	73	5265.0	21.36

AL Type	Torque		Max. rpm	D	L	L1	L2	d		GD kgf cm	Weight kgf
	Min.	Max.						Min.	Max.		
<b>AL - 035</b>	0.05	0.15	6,000	16.1	20.5	6.5	7.5	4	8	0.03	0.02
<b>AL - 050</b>	0.15	0.45	4,500	27	43.2	15.5	12.2	6	16	0.2	0.06
<b>AL - 070</b>	0.3	0.9	3,600	35	49.2	18.5	12.2	6	20	0.7	0.12
<b>AL - 075</b>	0.5	1.5	3,600	45	54.4	21	12.4	8	26	2.1	0.21
<b>AL - 090</b>	0.8	2.4	3,000	54	55	21	13	10	28	4.5	0.31
<b>AL - 095</b>	1.0	3.0	3,000	55	61	24	13	10	28	5.5	0.36
<b>AL - 100</b>	2.0	7.5	3,000	66	88	35	18	12	36	17.0	0.78
<b>AL - 110</b>	5.0	15.0	2,500	85	110	44	22	12	48	56.0	1.56

